

These high performance low noise amplifiers are designed to be antenna mounted.

STANDARD FEATURES


- Weatherproof enclosure
- Ultra low noise performance
- Internal voltage regulation
- Wide input voltage range
- Power thru RF connector or MS connector
- Operates from -40°C to $+70^{\circ}\text{C}$

OPTIONS

- 40, 50, 60 dB Gain
- SMA output connector
- Higher Output $P_{1\text{dB}}$ compression points



Outline: Standard Configuration



AK120000 Series

Ku Band SATCOM LNAs

Parameter	Notes	Limits	Units
Frequency Range	Band 01	10.95—12.75	GHz
	Band 02	10.70—12.75	GHz
Noise Temperature Selection	At 23°C case.	60, 65 max.	K
Gain	40, 50 dB min. optional	60 min., 64 typ.	dB
Gain Flatness	Full Band, Band 01	+/-0.5	dB
	Full Band, Band 02	+/-0.75	dB
Gain Slope	Per 40 MHz	+/-0.2	dB
Gain Stability vs. Time (Constant Temperature)	Short Term (10 min.)	+/-0.1	dB
	Medium Term (24 hours)	+/-0.2	dB
	Long Term (1 week)	+/-0.5	dB
Gain Stability	Versus temperature	-0.06 typ.	dB/°C
VSWR	Input	1.20typ., 1.25 max.	:1
	Output	1.25 typ., 1.50 max.	:1
Power Output @ 1 dB Compression	Standard	+10 min., +15 typ.	dBm
	Optional (High Power)	see options.	dBm
Third Order Output Intercept Point	Standard	+20 min., +25 typ.	dBm
	Optional (High Power)	see options.	dBm
Group Delay per 40 MHz	Linear	0.01 max.	nS/MHz
	Parabolic	0.001 max.	nS/MHz ²
	Ripple	0.1 max.	nS p-p
AM/PM Conversion	At -5 dBm output power	0.05 max.	°/dB
Maximum Input Power	Damage threshold	0 max.	dBm
	Input Desens. (13.75-14.50 GHz)	-30 max.	dBm
Power Requirements	Operating Voltage	+10 to +35	VDC
	Input Power (+10 dBm output)	1.9 nom.	Watts
	Input Power (+20 dBm output)	2.7 nom.	Watts
Mechanical Characteristics			
Size		See Outline on Page 1	
Weight		1.1 nom.	lbs.
Connectors	RF Input	WR75 WG (WR75 Cover Flange)	
	RF Output	Type N Female	
	Power/Alarm	MS3112E10-6P (mate supplied)	
Pressure Test		5 min.	Psi
Environmental			
Operating Temperature		-40 to +70	°C
Humidity	with condensation	100	%

User is responsible for sealing all connectors with appropriate weatherproofing materials. Failure to seal connectors will void warranty for any damage that might occur.

©2015 Geosync Microwave. All rights reserved.


Geosync Microwave reserves the right to make any changes to its products and specifications at any time and without notice.

AK120000 Series

Ku Band SATCOM LNAs

Part Number Configurator:

AK12XXXXXXXXXX



Part Number Example:

AK1201606510000

Freq: 10.95-12.75 GHz

Gain: 60 dB

Noise Temperature: 65K

Output Power: +10 dBm

Finish: White Paint

Output Connector: N Female

Voltage: +10 to +30 VDC

